


Thank you for purchasing a Screen Technics Swing Down Flat Panel Lift, please ensure that you read the following instructions fully before attempting to install this product.




NOTE: THIS SWING UTILISES AN ADVANCED FALL ARRESTOR SYSTEM, THE SWING DOWN CAN ONLY BE OPERATED IN A HORIZONTAL POSITION, IF THE SWING DOWN IS OPERATED ON ITS SIDE OR NOT IN A HORIZONTAL POSITION, THE ANTI-FALL DEVICE WILL LOCK AND DISCONNECT POWER. IF THE ANTI-FALL DEVICE IS ACTIVATED, IT WILL REQUIRE REPLACEMENT.

1. CONTROL

- Supplied with a Connect motor controller
- Infra-Red operation
- 2 x Dry Contact close inputs Up/Down


2. 4 CORE WIRING WAGO CONNECTOR

- Pin 1 – Brown Down
- Pin 2 – Black Up
- Pin 3 – Yellow / Green Earth
- Pin 4 – Blue Neutral





3. INSTALLATION EXAMPLES

- Bolted to timber in ceiling, attached to ceiling structure




- Attached to cable or chain to a suitable structure within ceiling space, using adjustable shackles for levelling




Continued Over.../

- Utilising 4 angle brackets, and mount using threaded rod



STEP 4. FITTING DOOR TO SWING DOWN

- The swing down door is packaged separately
- The door bracket is pre-set at the factory at 90 degrees, as shown below
- This will allow the fitting or removal of the door. Should the door require removal, the door must not exceed 90 degrees
- After the door is hung using the hook system
- Fit the 6 side bolts with tube spacers to hold door in place




Door hook system with bolts and spacers shown



Swing Down Door

STEP 5. LIMIT SETTING

- Limit are accessible from slot inside swing down
- Limit towards the front adjusts top limit / closed - **This limit should not be adjusted as damage to the panel may occur**
- Limit towards the back adjusts the bottom limit / open



ALWAYS ALLOW FOR PRODUCT REMOVAL IN ORDER TO BE SERVICED AND MAINTAINED.

Should you have any questions regarding the installation of our products please call our sales desk on +61 2 4869 2100 for assistance